



## FACT SHEET – Level It Concrete Floor Resurfacer 20kg



### Main Advantages

Level It Concrete Floor Resurfacer is an industrial grade overcoat for rough or damaged concrete.

- Level It can be overpainted if desired, with an epoxy resin coating such as Floorpaint Express Garacoat
- 20 kg of Level It will cover approximately 3m<sup>2</sup> at 3mm thickness and 0.9 m<sup>2</sup> at 10mm thickness



**Heavy Wear**



**Indoors and Out**



**Drying Time**

After approximately six hours the surface will accept foot and light traffic and is fully set in a maximum of 36 hours at a depth of 5mm.

#### Why Level It Concrete Floor Resurfacer?

Level It Concrete Floor Resurfacer will set to a smooth dust resistant surface that is so tough you can drive your car onto it. It is great for drives, paths, basements, garages, cellars – anywhere that concrete gets a bashing. The only things we don't recommend it for are very smooth concrete or powerfloated surfaces.

#### Prepare It

The concrete surface should be reasonably clean. Usually a good sweep with a stiff broom is sufficient. The surface can be damp, but not wet. If the surface is painted then remove as much paint as possible and any flaky paint. Any grease and oil should be removed with Clean It Degreaser.

#### Prime It

We supply 2 primers with this product. If the concrete is very dry, or the temperature is very warm, dampen with clean cold water. Apply Primer 1 with a soft broom or brush. It's best to leave Primer 1 overnight to seal and bind the surface, but if you are short of time you can leave it for as little as one hour. Then apply Primer 2, which can be applied when Primer 1 is tacky or dry – it doesn't matter. We supply a generous amount of the Primer 2 in case surfaces are porous and absorb more of the substance. If that isn't the case then it is usual to have some Primer 2 left over. Don't use too much of the primer or it may seep through the Level It Concrete Floor Resurfacer and if you are going to paint over Level It then it may lead to a patchy finish, if over primed.

#### Mix It

As soon as you've applied Primer 2 it is time to mix the product. Pour the contents of the resin bottle into the bucket and gradually add the powder and mix until even with a slow speed drill fitted with a mixing blade. Work the mixing blade around the base and sides of the container. You'll know you're finished when an even colour and creamy consistency is achieved (normally not more than five minutes).

#### Apply It

Pour the product onto the area you've primed and spread with a trowel. It is quite flowable, but just needs a bit of help up to edges and into corners. To remove any air you'll need a spiked roller, which we can

supply – it really is that simple. Don't use the spiked roller for more than 20 minutes as the mixture will be starting to set.

Try not to tread primer or the mixture into surrounding areas as they will be difficult to remove.

Please don't apply Level It Concrete Floor Resurfacer at temperatures less than 5°C or more than 30°C. Temperatures about 25°C can make the product sticky and cause fine cracks to appear when set.

#### Paint It?

Level It Concrete Floor Resurfacer doesn't need to be overpainted, but can be if desired. We do not recommend that you use concrete floor paint as new Level It has residual alkalinity which adversely affects the paint. We recommend that you use a solvent free two part epoxy coating such as Floorpaint Express Garacoat.

#### Clean It

Clean your equipment in water before the product starts to set. When fully set, Level It can be cleaned with detergents or degreasers, such as Clean It Floor Degreaser. Floors should never be cleaned at temperatures of 60°C or above when Level It has been applied.

#### You'll need

Mixing Blade  
Spiked Roller  
Telescopic handle (for spiked roller)  
10" Steel Float

These products are available on our website and can be shipped with your order for Level It so you can get the job done quickly.

#### Disposal and Safety Information

Please see the *Material Safety Data Sheet* at [www.floorpaintexpress.co.uk](http://www.floorpaintexpress.co.uk) for safety information.

#### Availability

Level It Concrete Floor Resurfacer is supplied in 20 kg containers. Available from [www.floorpaintexpress.co.uk](http://www.floorpaintexpress.co.uk)

## Call us now for deals and support

Tel: 0845 894 0703 Email: [info@floorpaintexpress.co.uk](mailto:info@floorpaintexpress.co.uk) Visit: [www.floorpaintexpress.co.uk](http://www.floorpaintexpress.co.uk)