



FACT SHEET – Block Seal 5L



Main Advantages

If your drive, or patio, is block paved, give it a treat with Block Seal block paving sealer, the easy-to-apply resin that gives a smart semi-gloss finish to block paving – wherever it is.

- Makes block paving look good
- Binds together the sand grains in the joints, helping to strengthen the paving
- Helps protect the paving stones from oil deposits from your car
- Slows down the rate at which weeds appear in the joints between the slabs

Why Block Seal?

It is easily applied by brush or roller and dries in about 4 hours to a tough surface, which means that the area you are working on won't be out of action for long.

Prepare It

Ensure that the surface to be worked on is clean, dry and free from dirt, dust, grease and other contaminants. If you are washing the area first then allow it to dry thoroughly before applying Block Seal.

If you have moss, algae or other fungi then it should be treated with a suitable algicide or fungicide.

To ensure the best possible finish, the joints in between the blocks should be filled with clean and dry compacted sand up to the bottom on the chamfer.

Cover It

Covers approximately 15m² per 5 litre pack, but this is dependent on the porosity and width of the blocks as well as joint width.

Only one coat is normally needed, but a second coat will give a shinier finish.

Apply a second coat after 4 hours, but within 48 hours, if required. Only apply in temperatures above 10°C and when rain is not forecast for at least 24 hours.



The Product

A semi-gloss clear resin in a moisture curing polyurethane solution, which aids quick setting.



Apply It

Apply Block Seal with a brush or roller and don't apply too thickly. Don't allow the product to gather in the joints or settle on the blocks.

Only take as much product as you need for a working quantity and re-seal the tin to stop moisture vapour getting to the mixture.



Drying Time

At 20°C Block Seal is touch dry in 2 hours and fully dry in 4 hours.

Store It

Fully close the container and store in a dry, cool and well ventilated area.

You'll Need

9" Roller and tray.
Brush (5")

Disposal and Safety Information

Please see the *Material Safety Data Sheet* at www.floorpaintexpress.co.uk for safety information.

Volatile Organic Compounds

EU limit for this Product) cat/h): 750g/L (2010).
This product contains less than 750g/L VOC.

Availability

Block Seal is supplied in 5 litre containers.
Available from www.floorpaintexpress.co.uk

Call us now for deals and support

Tel: 0845 894 0703 Email: info@floorpaintexpress.co.uk Visit: www.floorpaintexpress.co.uk