



FACT SHEET – Drive Grip Slip Resistant Paint 5L



Main Advantages

Not only will Drive Grip Slip Resistant Paint keep your concrete and asphalt looking good, it will help keep the people that walk on it on their feet.

- Use on asphalt or concrete
- No need to prime
- Easy to apply with only one coat normally required

- A pre-mixed aggregate in the paint gives great slip resistance and saves you time as you don't need to mix it in yourself



The Product

A matt paint that has a lightly textured surface that provides slip resistance on asphalt, tarmac and porous concrete.



Indoors and Out



Slip Resistant

Why Drive Grip Slip Resistant Paint?

Wherever you have concrete or asphalt then eventually it will need brightening. The two criteria to use are safety and smartness.

Drive Grip Slip Resistant Paint scores on both counts as it not only looks good, it is an anti slip paint that will help prevent dangerous slips and trips. The 'secret' ingredient is a light aggregate that is pre-mixed into the paint, which gives it strong anti slip properties.

It can transform a garage, drive or cellar and leave you safe in the knowledge that it protects people as well as flooring. It has very good ultra-violet light resistance which will prevent fading if used outdoors.

Prepare It

The surface to be painted should be clean and dry; although slightly damp isn't a problem. If there is oil, grease or other contaminants then use Clean It Floor Degreaser to remove them.

You can paint over an existing painted surfaces, though where the paint is flaky this should be sanded off so the new paint can adhere.

Apply It

Stir well before use.

You can apply Drive Grip Slip Resistant Paint with a brush or roller. Only one coat is normally needed, but you may need a second on porous or rough surfaces. If so, it can normally be applied after about an hour depending on conditions.

There is no need to apply the paint too thickly. The texture develops as the paint dries, so don't worry if it isn't immediately apparent.

If you are using externally then do not apply if rain or frost are forecast, or when temperatures fall below 10°C or are above 30°C.

Note: This product is not recommended for use on Stamped/Imprinted concrete (the type designed to look like paving or cobbles). These surfaces are too smooth and non-porous for the coating to bond properly.

Cover It

Covers approximately 15-20m² per 5 litres.

Clean It

Clean brushes and rollers in warm soapy water before the paint starts to dry.

Drying Time

Within 24 hours the painted area can be used for light traffic and is back to full use in 48 hours (these times will be extended when the weather is cold, damp or humid).

Storage and Shelf Life

Store in a cool, dry place away from direct sunlight. The shelf life is at least one year when unopened.

You'll need

9" Roller and tray

Spare roller

5" Brush

These products are available on our website and can be shipped with your order for Drive Grip so you can get the job done quickly.

Important

Only use on well drained surfaces and do not apply in areas that are normally under water, as this could actually mean the product could contribute to a slip hazard rather than prevent one.

Do not overfill asphalt or tarmac, as this will not only extend drying times, but can reduce the drainage capability of the surface which may cause a slip hazard in the wet. This will also reduce the coverage of the product dramatically.

Disposal and Safety Information

Please see the Material Safety Data Sheet at

www.floorpaintexpress.co.uk for safety information.

Availability

Drive Grip Slip Resistant Paint is supplied in 5 litre containers.

Available from www.floorpaintexpress.co.uk

Colour Range



True Blue

Brick Red

Stone Grey

White

Black

Call us now for deals and support

Tel: 0845 894 0703 Email: info@floorpaintexpress.co.uk Visit: www.floorpaintexpress.co.uk