

### FACT SHEET – Seal 'n' Tint Decorative Concrete Stain 5L



#### Main Advantages

Seal 'n' Tint is the easy way to give drab, grey concrete or old paving slabs a new lease of life and add some colour. Drives, paths, patios, porches, basements, garages, cellars, swimming pool surrounds and more will really benefit from a smartening up. Two coats are recommended, but you can create different effects, or depths of colour, by applying more coats. It has the added advantage of eliminating dust and making surfaces easier to clean.



#### The Product

A tinted liquid which dries to a coloured low sheen finish. The more coats you apply, the darker the final result will be. Use indoors or outside.



#### Solvent Free



#### Drying Time

You will be able to walk on a surface treated with Seal 'n' Tint or re-coat in about 12-16 hours, based on a minimum temperature of 15°C. The lower the temperature, the longer the drying time. The product will be fully resistant to scuffing in 7 days at 15°C.

- Requires minimal preparation
- Is easy to apply with a brush or roller
- Choice of exciting colours

- Long lasting
- Stops concrete from dusting
- Solvent free, no smell during application

#### Why Seal 'n' Tint?

Tinting concrete is all the rage in America and is starting to catch on in the UK. If you are looking for something different that will enhance the look of concrete then Seal 'n' Tint is for you.

#### Prepare It

Preparation time is minimal, depending on the condition of your concrete.

Surfaces will need to be clean and dry and not have any loose material. This product is designed for absorbent concrete surfaces, so if your concrete or concrete slabs have been painted or sealed then you will need to remove these coatings before applying Seal 'n' Tint. If the concrete has surface grease or oil then our degreaser Clean It should be applied. Give everything a good sweep with a stiff broom and you are ready to go.

It is best not to wash the surface if it is very absorbent as it will absorb too much water and Seal 'n' Tint should only be applied to a dry surface.

#### Apply It

Making sure the lid is on tight, give the tin a good shake.

Apply in dry, warm (above 10°C) conditions. Good ventilation helps the product to dry. Pour some into a roller tray. Don't pour directly onto your concrete as this may create a patchy effect. Use a medium pile roller to apply to the bare, dry concrete. Apply sparingly at first to make sure you are achieving the desired result. A paint brush or mini roller will help with edges or small areas.

If using a paint brush you can use straight from the tin. Avoid runs on vertical surfaces as this may cause a darker stain.

Work the liquid into the surface as evenly as you can. Apply more as necessary if you find you have very porous concrete and the coating is sinking in.

Don't overload your brush or roller. If it drips Seal 'n' Tint will stain, which isn't serious, but means you will have to put another coat on to compensate.

#### Cover It

5 litres (1 gallon) of Seal 'n' Tint will cover approximately 37 square metres (400 square feet) with one coat. We recommend you apply a minimum of two coats, leaving 12 hours between coats. If your concrete is very absorbent you may need a third.

#### Store It

Seal 'n' Tint should be stored at a temperature above 15°C for a minimum of 8 hours before use. For normal storage, keep away from direct sunlight and store in a cool, dry place in unopened containers. This product must not be allowed to freeze.

#### Clean It

Remove as much of the product as possible before washing brushes, rollers and trays in water.

#### Don't Use

Don't use Seal 'n' Tint on concrete that is less than 28 days old.


#### Disposal and Safety Information

Please see the Material Safety Data Sheet at [www.floorpaintexpress.co.uk](http://www.floorpaintexpress.co.uk) for safety information.

#### Availability

Seal 'n' Tint Decorative Concrete Stain is supplied in 5 litre containers. Available from [www.floorpaintexpress.co.uk](http://www.floorpaintexpress.co.uk)

#### Colour Range



## Call us now for deals and support

Tel: 0845 894 0703 Email: [info@floorpaintexpress.co.uk](mailto:info@floorpaintexpress.co.uk) Visit: [www.floorpaintexpress.co.uk](http://www.floorpaintexpress.co.uk)